

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number  
**WO 2005/095997 A1**

(51) International Patent Classification<sup>7</sup>: **G01P 15/08**,  
15/12, G01L 1/22

(CH). **JUNGEN, Alain** [LU/CH]; Bülachstrasse 3a,  
CH-8057 Zürich (CH). **STAMPFER, Christoph** [IT/IT];  
Kühbachweg, 18, I-39050 Völs Am Schlern (IT).

(21) International Application Number:  
PCT/EP2004/014570

(74) Agent: **KLEY, Hansjörg**; c/o Siemens AG, Postfach 22  
16 24, 80506 München (DE).

(22) International Filing Date:  
22 December 2004 (22.12.2004)

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
04004883.7 2 March 2004 (02.03.2004) EP

(71) Applicant (for all designated States except US): **ETH  
ZÜRICH** [CH/CH]; Eth Transfer, Rämistrasse 101,  
CH-8092 Zürich (CH).


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HIEROLD,  
Christofer** [DE/CH]; Eilweg 5, CH-8634 Hombrechtikon

[Continued on next page]

(54) Title: FORCE SENSOR



(57) Abstract: The resolution and the signal-to-noise ration of known force sensors as e.g. capacitive force sensors decrease when scaling them down. To solve this problem there is a solution presented by the usage of a nanostructure as e.g. a carbo nanotube, which is mechanically deformed by a force to be measured. The proposed force sensors comprises a support with two arms carrying the carbon nanotube. The main advantage of this force sensor is a very high sensitivity as the conductance of carbon nanotubes changes several orders of magnitude when a mechanical deformation arises.

WO 2005/095997 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

— with amended claims and statement

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*